(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 15 June 2006 (15.06.2006)

(10) International Publication Number WO 2006/061679 A3

(51) International Patent Classification: H02M 7/48 (2006.01)

(21) International Application Number:

PCT/IB2005/003127

(22) International Filing Date: 20 October 2005 (20.10.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 21 October 2004 (21.10.2004) JP 2004-306547

(71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; No.2, Tama-cho, Kangawa-ku, Yokohama-shi, Kanagawa-ken (JP).

(72) Inventors: and

Inventors/Applicants (for US only): YOSHIMOTO, Kantaro [JP/JP]; 1-38 Uenomachi, Naka-ku, Yoko-Kanagawa 231-0842 (JP). KITAJIMA, hama-shi. Yasuhiko [JP/JP]; 1189-4-4041 Okamoto, Kamakura-shi, Kanagawa 247-0072 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of
- (88) Date of publication of the international search report: 17 August 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: POWER CONVERTER AND CONTROL METHOD FOR A POWER CONVERTER



(57) Abstract: A control method for a power converter capable of reducing overall volume of a system and energy loss by using a plurality of power sources and distributing loads to them without a DCDC converter and a combination of a fuel cell and a battery. The power converter has DC power sources, and poles formed by connecting various poles of the DC sources. Voltage is applied to a load by switching between poles. The method includes determining conductivity for a switch between poles of said first DC power source when a voltage command is lower than the electric potential output by said second DC power source; determining conductivity for a switch between the poles of said second DC source when the voltage command is higher than the electric potential output by said second DC source; and switching the pole to be connected to said load in accordance with the determinations.

